

INDUSTRIAL COMPONENT DATA

SPB-D-125 248145 EATON ELECTRIC Lead-through terminal for B-type arresters, 125A, 500V AC/DC, overvoltage ca..

Brand: EATON - MOELLER | Manufacturer Part Number: SPB-D-125



Manufacturer	EATON - MOELLER
MPN / Reference	SPB-D-125
Catalog number	248145
Category	Auxiliary device for distribution board devices
Minimum order	1 Pcs
Document ID	EO-9E1737ABCA
Generated	2026-08-05

Product Overview

Lead-through terminal for B-type arresters, 125A, 500V AC/DC, overvoltage category III

Lead-through terminal for B-type arresters, rated operational current 125A, rated operating voltage 500V AC/DC, overvoltage category III, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 0.5-35 mm² solid / 0.5-25 mm² flexible, type conform to IIEC 61643-1: 1998-02, EDIN VDE 0675 part6: 1989-11, IEC 61024-1: 1990-03, IEC 60947-7-1: 1989-10, DIN VDE 0110-1: 1997-04

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

Lead-through terminal for B-type arresters, 125A, 500V AC/DC, overvoltage category III Lead-through terminal for B-type arresters, rated operational current 125A, rated operating voltage 500V AC/DC, overvoltage category III, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 0.5-35 mm² solid / 0.5-25 mm² flexible, type conform to IIEC 61643-1: 1998-02, EDIN VDE 0675 part6: 1989-11, IEC 61024-1: 1990-03, IEC 60947-7-1: 1989-10, DIN VDE 0110-1: 1997-04 [Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdis] 0 W Operating ambient temperature min. -40 °C Operating ambient temperature max. +85 °C 0 , Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component /

Auxiliary contact unit for distribution board ( [AKE327013]) Device fitting Other Additional equipment Other
Attached at delivery No Assembly width (TE) 1 Number of contacts as normally open contact Number of contacts as
normally closed contact Number of contacts as change-over contact Number of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPB-D-125 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.