

INDUSTRIAL COMPONENT DATA

SP-B+C/3+1 267510 EATON ELECTRIC Surge arrester set, TN-S/TT set, 3+Npole

Brand: EATON - MOELLER | Manufacturer Part Number: SP-B+C/3+1



Manufacturer	EATON - MOELLER
MPN / Reference	SP-B+C/3+1
Catalog number	267510
Category	Combined arrester for power supply systems
Minimum order	1 Pcs
Document ID	EO-3EB3FC3BB0
Generated	2026-08-05

Product Overview

Surge arrester set, TN-S/TT set, 3+Npole

Surge arrester: applied in accordance with IEC60364-5-53 Clause 534 For protection of consumer systems

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Surge arrester set, TN-S/TT set, 3+Npole Surge arrester: applied in accordance with IEC60364-5-53 Clause 534 For protection of consumer systems [Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W

Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 3 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -40 °C Operating ambient temperature max. +70 °C , Technical data ETIM 7.0

Earthing, lightning and surge protection (EG000021) / Combined arrester for power supply systems (EC001457) Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Combined lightning current/surge arrester f. power supply s. () [ACN284011]

System configuration DC No System configuration IT Yes System configuration TN Yes System configuration TN-C No System configuration TN-C-S Yes System configuration TN-S Yes System configuration TT Yes System configuration other No Number of poles 4 Lightning impulse current (10/350 µs) 35 kA Max. continuous voltage AC 0 V Max. continuous voltage DC 0 V Nominal voltage AC 0 V Nominal voltage DC 0 V Max. PV-voltage 0 V Voltage protection level 1.5 kV Voltage protection level L-N 0 kV Voltage protection level L-PE kV Voltage protection level N-PE 0 kV Voltage....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SP-B+C/3+1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.