

**INDUSTRIAL COMPONENT DATA**

# SWD4-10LR4P-2R 183226 Y7-183226 EATON ELECTRIC MB-Power-cable IP67 for connecting the Multiblock, 10 m, pref..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-10LR4P-2R



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | EATON - MOELLER              |
| MPN / Reference | SWD4-10LR4P-2R               |
| Catalog number  | Y7-183226                    |
| Category        | Data and communication cable |
| Minimum order   | 1 Pcs                        |
| Document ID     | EO-693AC1D98B                |
| Generated       | 2026-08-06                   |

## Product Overview

MB-Power-cable IP67 for connecting the Multiblock, 10 m, prefabricated with 7/8" plug and 7/8" socket  
SWD4-10LR4P-2R

Eaton SWD4 MB-Power-cable, IP67, 10 m, 4 pole, Prefabricated with 7/8" right-angle plug and 7/8" right-angle socket  
4 pole MB-Power-cable IP67 degree of protection for connecting the Multiblock I/O module, Cable 10 m length,  
Prefabricated with 7/8z right-angle plug and 7/8z right-angle socket

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                    |
|--------------|------------------------------------|
| Catalog path | EATON - MOELLER > Smartwire Darwin |
|--------------|------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory MB-Power-cable Catalog Number 183226 Model Code SWD4-10LR4P-2R EAN 4015081781591 Product Length/Depth 307.692 mm Product Height 76.923 mm Product Width 307.692 mm Product Weight 1.636 kg Certifications UL

CSA Catalog Notes Condensation: permissible Features & Functions

Features Oil resistant (acc. EN 60811-404)

Oil resistant (acc. IEC 60811-404)

Radial water blocking cable

UV resistant Fitted with: 7/8" right-angle socket

7/8" right-angle plug Functions For directly connecting the power supply to EU6E..., EU8E.. IP67 SmartWire-DT modules  
General

Cable length 10 m Number of Poles Four-pole Outer diameter - approximate 11 mm Outer sheath material Polyvinyl chloride (PVC) Permitted bending radius, moving application with forced guidance - min 0 mm Product category

SmartWire-DT accessories Suitable as Signaling cable Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Safety

Flame retardant In accordance with EN 60332-1-2 Design verification

Equipment heat dissipation, current-dependent P<sub>vid</sub> 0 W Heat dissipation capacity P<sub>diss</sub> 0 W Heat dissipation per pole, current-dependent P<sub>vid</sub> 0 W Rated operational current for specified heat dissipation (I<sub>n</sub>) 0 A Static heat dissipation, non-current-dependent P<sub>vs</sub> 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's r...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-10LR4P-2R with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.