

INDUSTRIAL COMPONENT DATA

SWD4-1LR5-S 174697 Y7-174697 EATON ELECTRIC Round Cable SWDT, 5-pole, 1.5 m, pre-fabricated with plug connec..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-1LR5-S



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-1LR5-S
Catalog number	Y7-174697
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-4EEC54C946
Generated	2026-08-06

Product Overview

Round Cable SWDT, 5-pole, 1.5 m, pre-fabricated with plug connector M12 male
SWD4-1LR5-S

Eaton SWD4 I/O round cable IP67, 1 m, 5-pole, Prefabricated with M12 plug

5-pole I/O round cable in safety class IP67 for direct connection of sensors / actuators, 5 open circuits, 1 m long, comes with M12 plug

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Smartwire Darwin

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Round cable Catalog Number 174697 Model Code SWD4-1LR5-S EAN 4015081711833 Product Length/Depth 1000 mm Product Height 16.3 mm Product Width 16.3 mm Product Weight 0.07 kg
Certifications UL

CSA Catalog Notes Condensation: permissible Features & Functions

Features Longitudinal water blocking cable

Oil resistant (acc. EN 60811-404)

Oil resistant (acc. IEC 60811-404)

Radial water blocking cable

UV resistant Fitted with: M12 plug, A-keyed, on one side Functions For directly connecting sensors/actuators to IP67 SWD modules General

Cable length 1 m Number of Poles Five-pole Outer diameter - approximate 5.6 mm Outer sheath material Polyvinyl chloride (PVC) Permitted bending radius, moving application with forced guidance - min 38 mm Product category SmartWire-DT accessories Suitable as Signaling cable Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Safety
Flame retardant In accordance with EN 60332-1-2 Design verification
Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-1LR5-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.