


INDUSTRIAL COMPONENT DATA

SWD4-20LR4P-S 183207 Y7-183207 EATON ELECTRIC MB-Power-cable IP67 for connecting the Multiblock, 20 m , pref..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-20LR4P-S



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-20LR4P-S
Catalog number	Y7-183207
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-FD84F204FD
Generated	2026-08-05

Product Overview

MB-Power-cable IP67 for connecting the Multiblock, 20 m , prefabricated with 7/8" plug

SWD4-20LR4P-S

Eaton SWD4 MB-Power-cable, IP67, 20 m, 4 pole, Prefabricated on one side with 7/8" straight socket

4 pole MB-Power-cable IP67 degree of protection for connecting the Multiblock I/O module, bare cables, 20 m long, Prefabricated with 7/8z plug

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory MB-Power-cable Catalog Number 183207 Model Code SWD4-20LR4P-S EAN 4015081781409 Product Length/Depth 307.692 mm Product Height 102.564 mm Product Width 307.692 mm Product Weight 3.273 kg Certifications CSA

UL Catalog Notes Condensation: permissible Features & Functions

Features Oil resistant (acc. EN 60811-404)

Oil resistant (acc. IEC 60811-404)

Radial water blocking cable

UV resistant Fitted with: 7/8" straight socket on one side Functions For directly connecting the power supply to EU6E..

EU8E.. IP67 SmartWire-DT modules General

Cable length 20 m Number of Poles Four-pole Outer diameter - approximate 11 mm Outer sheath material Polyvinyl chloride (PVC) Permitted bending radius, moving application with forced guidance - min 0 mm Product category SmartWire-DT accessories Suitable as Signaling cable Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Safety

Flame retardant In accordance with EN 60332-1-2 Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements.....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-20LR4P-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.