


INDUSTRIAL COMPONENT DATA

SWD4-2LR4P-2S 183212 Y7-183212 EATON ELECTRIC MB-Power-cable IP67 for connecting the Multiblock, M 2, prefab..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-2LR4P-2S



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-2LR4P-2S
Catalog number	Y7-183212
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-41DB80ED26
Generated	2026-08-05

Product Overview

MB-Power-cable IP67 for connecting the Multiblock, M 2, prefabricated with 7/8" plug and 7/8" socket
SWD4-2LR4P-2S

Eaton SWD4 MB-Power-cable, IP67, 2 m, 4 pole, Prefabricated with 7/8" plug and 7/8" socket

4 pole MB-Power-cable IP67 degree of protection for connecting the Multiblock I/O module, Cable 2 m length, Prefabricated with 7/8z plug and 7/8z socket

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory MB-Power-cable Catalog Number 183212 Model Code SWD4-2LR4P-2S EAN 4015081781454 Product Length/Depth 307.692 mm Product Height 51.282 mm Product Width 307.692 mm Product Weight 0.409 kg Certifications CSA

UL Catalog Notes Condensation: permissible Features & Functions

Features Longitudinal water blocking cable

Oil resistant (acc. EN 60811-404)

Oil resistant (acc. IEC 60811-404)

Radial water blocking cable Fitted with: 7/8" plug

7/8" socket Functions For directly connecting the power supply to EU6E.., EU8E.. IP67 SmartWire-DT modules General
Cable length 2 m Number of Poles Four-pole Outer diameter - approximate 11 mm Outer sheath material Polyvinyl chloride
(PVC) Permitted bending radius, moving application with forced guidance - min 0 mm Product category SmartWire-DT
accessories Suitable as Signaling cable Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Safety
Flame retardant In accordance with EN 60332-1-2 Design verification
Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdiss 0 W Heat dissipation per pole,
current-dependent Pvid 0 W Rated operational current for specified heat dissipation (In) 0 A Static heat dissipation,
non-current-dependent Pvs 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1
Verification of thermal stability of enclosures Meets the product standard's requir...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-2LR4P-2S with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.