

INDUSTRIAL COMPONENT DATA

SWD4-2LR5-1-2S 179546 Y7-179546 EATON ELECTRIC Round Cable for devices SWDT, IP67, 5-pin, 2 m, prefabricated..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-2LR5-1-2S



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-2LR5-1-2S
Catalog number	Y7-179546
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-4AAE1B8940
Generated	2026-08-06

Product Overview

Round Cable for devices SWDT, IP67, 5-pin, 2 m, prefabricated with plug connector M12 male and M12 female SWD4-2LR5-1-2S

Eaton SWD4 I/O-Device connection cable IP67, 5-pole, M 2, Prefabricated with M12 plug and M12 socket

5 pole I/O device connection round cable with IP67 degree of protection 2 m long, prefabricated with M12 plug and M12 socket

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Round connection cable Catalog Number 179546 Model Code SWD4-2LR5-1-2S EAN 4015081746323 Product Length/Depth 2000 mm Product Height 16.3 mm Product Width 16.3 mm Product Weight 0.12 kg Certifications CSA

UL Catalog Notes Condensation: permissible Features & Functions

Features Longitudinal water blocking cable

Oil resistant (acc. EN 60811-404)

Oil resistant (acc. IEC 60811-404)

Radial water blocking cable Fitted with: M12 plug, A-keyed

M12 socket Functions For directly connecting sensors/actuators to IP67 SWD modules General

Cable length 2 m Number of Poles Five-pole Outer diameter - approximate 4.55 mm Outer sheath material Polyurethane

(PUR) Permitted bending radius, moving application with forced guidance - min 38 mm Product category SmartWire-DT accessories Suitable as Signaling cable Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Safety

Flame retardant In accordance with EN 60332-1-2 Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Ve...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-2LR5-1-2S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.