

INDUSTRIAL COMPONENT DATA

SWD4-2LR5-S 174698 Y7-174698 EATON ELECTRIC Round Cable SWDT, 5-pin, 2 m, prefabricated with plug connector ..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-2LR5-S



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-2LR5-S
Catalog number	Y7-174698
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-7A4C208315
Generated	2026-08-06

Product Overview

Round Cable SWDT, 5-pin, 2 m, prefabricated with plug connector M12 male
SWD4-2LR5-S

Eaton SWD4 I/O round cable IP67, 2 m, 5-pole, Prefabricated with M12 plug
5-pole I/O round cable in safety class IP67 for direct connection of sensors / actuators, 5 open circuits, 2 m long, comes with M12 plug

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Smartwire Darwin**

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Round cable Catalog Number 174698 Model Code SWD4-2LR5-S EAN 4015081711840 Product Length/Depth 2000 mm Product Height 16.3 mm Product Width 16.3 mm Product Weight 0.12 kg
Certifications CSA
UL Catalog Notes Condensation: permissible Features & Functions
Features Longitudinal water blocking cable
Oil resistant (acc. EN 60811-404)
Oil resistant (acc. IEC 60811-404)
Radial water blocking cable Fitted with: M12 plug, A-keyed, on one side Functions For directly connecting sensors/actuators to IP67 SWD modules General
Cable length 2 m Number of Poles Five-pole Outer diameter - approximate 5.6 mm Outer sheath material Polyvinyl chloride

(PVC) Permitted bending radius, moving application with forced guidance - min 38 mm Product category SmartWire-DT accessories Suitable as Signaling cable Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Safety

Flame retardant In accordance with EN 60332-1-2 Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verificat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-2LR5-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.