

INDUSTRIAL COMPONENT DATA

SWD4-4LR5-2S 174767 Y7-174767 EATON ELECTRIC

SmartWire-DT round cable IP67, 4 meters, 5-pole, Prefabricated ..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-4LR5-2S



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-4LR5-2S
Catalog number	Y7-174767
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-E75609E583
Generated	2026-08-06

Product Overview

SmartWire-DT round cable IP67, 4 meters, 5-pole, Prefabricated with M12 plug and M12 socket

SWD4-4LR5-2S

5 pole SmartWire-DT round cable with IP67 degree of protection 4 m long, prefabricated with M12 plug and M12 socket

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Round cable Catalog Number 174767 Model Code SWD4-4LR5-2S EAN

4015081712533 Product Length/Depth 4000 mm Product Height 16.3 mm Product Width 16.3 mm Product Weight 0.22 kg

Certifications UL

CSA Catalog Notes Condensation: permissible Features & Functions

Features Oil resistant (acc. EN 60811-404)

Oil resistant (acc. IEC 60811-404)

Radial water blocking cable Fitted with: M12 socket

M12 plug, A-keyed Functions For connecting peripheral SmartWire-DT cards General

Cable length 4 m Number of Poles Five-pole Outer diameter - approximate 5.6 mm Outer sheath material Polyvinyl chloride (PVC) Permitted bending radius, moving application with forced guidance - min 46 mm Product category SmartWire-DT

accessories Suitable as Signaling cable Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Safety

Flame retardant In accordance with EN 60332-1-2 Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-4LR5-2S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.