

INDUSTRIAL COMPONENT DATA

**SWD4-M3LR5-1-2S 179543 Y7-179543 EATON ELECTRIC
Round Cable for devices SWDT, IP67, 5-pin, 0.3 m, pre-fabric..**

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-M3LR5-1-2S



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-M3LR5-1-2S
Catalog number	Y7-179543
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-DC87D97277
Generated	2026-08-06

Product Overview

Round Cable for devices SWDT, IP67, 5-pin, 0.3 m, pre-fabricated with plug connector M12 male and M12 female
SWD4-M3LR5-1-2S

Eaton SWD4 I/O-Device connection cable IP67, 5-pole, 0.3 m, Prefabricated with M12 plug and M12 socket
5 pole I/O device connection round cable with IP67 degree of protection 0.3 m long, prefabricated with M12 plug and M12 socket

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Smartwire Darwin

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Round connection cable Catalog Number 179543 Model Code SWD4-M3LR5-1-2S
EAN 4015081746293 Product Length/Depth 300 mm Product Height 16.3 mm Product Width 16.3 mm Product Weight 0.04
kg Certifications UL

CSA Catalog Notes Condensation: permissible Features & Functions

Features Oil resistant (acc. EN 60811-404)

Oil resistant (acc. IEC 60811-404)

Radial water blocking cable

UV resistant Fitted with: M12 plug, A-keyed

M12 socket Functions For directly connecting sensors/actuators to IP67 SWD modules General

Cable length 0.3 m Number of Poles Five-pole Outer diameter - approximate 4.55 mm Outer sheath material Polyurethane

(PUR) Permitted bending radius, moving application with forced guidance - min 38 mm Product category SmartWire-DT accessories Suitable as Signaling cable Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Safety

Flame retardant In accordance with EN 60332-1-2 Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-M3LR5-1-2S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.