

INDUSTRIAL COMPONENT DATA

SWD4-PRF5-2-S 179541 Y7-179541 EATON ELECTRIC

SmartWire-DT housing bushing socket M12, 5 cables, 0.15 m long

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-PRF5-2-S



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-PRF5-2-S
Catalog number	Y7-179541
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-313B57BCFA
Generated	2026-08-06

Product Overview

SmartWire-DT housing bushing socket M12, 5 cables, 0.15 m long

SWD4-PRF5-2-S

SmartWire-DT housing penetration, 5 pole M12 socket with IP67 degree of protection, 1/2z enclosure cable gland with 5 cables, 0.15 m long

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Housing bushing socket Catalog Number 179541 Model Code SWD4-PRF5-2-S

EAN 4015081746279 Product Length/Depth 148 mm Product Height 24 mm Product Width 24 mm Product Weight 0.045 kg

Certifications IEC/EN 61131-2

UL

EN 50178

CSA Catalog Notes not relevant General

Degree of protection IP20

IP20 (according to IEC/EN 60529, EN 50178, VBG 4) Product category SmartWire-DT accessories Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Mounting position As required Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Dry heat to IEC 60068-2-2

Damp heat, constant, to IEC 60068-2-3 Environmental conditions Condensation: prevent with appropriate measures

Operating temperature - min -25 °C Operating temperature - max 70 °C Relative humidity 5 - 95 % (non-condensing, IEC/EN 60068-2-30) Communication

Connection type SWD-IN, I/O: 5 cables

M12 socket (A-keyed), 5 pole Input/Output

Number of insertion cycles 500 Design verification

Heat dissipation capacity P_{diss} 0 W Static heat dissipation, no...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-PRF5-2-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.