

INDUSTRIAL COMPONENT DATA

SWD4-PRM5-1-S 174759 Y7-174759 EATON ELECTRIC

SmartWire-DT housing bushing plug M12, 5 cables, 1 m long

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-PRM5-1-S



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-PRM5-1-S
Catalog number	Y7-174759
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-95201BCF2A
Generated	2026-08-06

Product Overview

SmartWire-DT housing bushing plug M12, 5 cables, 1 m long

SWD4-PRM5-1-S

SmartWire-DT housing penetration, 5 pole M12 plug with IP67 degree of protection, 1/2z enclosure cable gland with 5 cables, 1 m long

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Housing bushing socket Catalog Number 174759 Model Code SWD4-PRM5-1-S
EAN 4015081712458 Product Length/Depth 1000 mm Product Height 25.4 mm Product Width 25.4 mm Product Weight
0.136 kg Certifications IEC/EN 61131-2

UL

EN 50178

CSA Catalog Notes not relevant General

Degree of protection IP20

IP20 (according to IEC/EN 60529, EN 50178, VBG 4) Product category SmartWire-DT accessories Ambient conditions,
mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz,
according to IEC/EN 61131-2, Vibrations Mounting position As required Shock resistance 15 g, Mechanical, according to

IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-3

Dry heat to IEC 60068-2-2 Environmental conditions Condensation: prevent with appropriate measures Operating temperature - min -25 °C Operating temperature - max 70 °C Relative humidity 5 - 95 % (non-condensing, IEC/EN 60068-2-30) Communication

Connection type Connection 1: M12 plug (A-keyed), 5 pole

SWD-OUT, I/O: 5 cables Input/Output

Number of insertion cycles 500 Design verification

Heat dissipation capacity P_{diss} 0 W Static he...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-PRM5-1-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.