

INDUSTRIAL COMPONENT DATA

SWD4-RC5-10 174754 Y7-174754 EATON ELECTRIC

Resistance terminator SWDT, for round cable, IP67, M12

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-RC5-10



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-RC5-10
Catalog number	Y7-174754
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-8951DBA666
Generated	2026-08-04

Product Overview

Resistance terminator SWDT, for round cable, IP67, M12

SWD4-RC5-10

Eaton SWD4 SmartWire-DT bus termination resistor IP67, M12

SmartWire-DT bus termination resistor with IP 67 degree of protection, connected to the 5-conductor round cable or directly to the SmartWire-DT T-connectors (I/O modules with IP67)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Smartwire Darwin

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Bus termination resistor Catalog Number 174754 Model Code SWD4-RC5-10 EAN 4015081712403 Product Length/Depth 25.65 mm Product Height 41 mm Product Width 20.06 mm Product Weight 0.01 kg Certifications CSA File No.: 2324643

EN 50178

IEC/EN 61131-2

UL File No.: E29184

UL Category Control No.: NKCR

UL

CSA

CSA Class No.: 3211-07 Features & Functions

Functions For IP67, M12 SWD bus termination General

Current consumption 17 mA, 24-V supply Degree of protection IP67

IP67 (according to IEC/EN 60529, EN 50178, VBG 4) Overvoltage category II Pollution degree 3 Product category

SmartWire-DT accessories Type SmartWire-DT bus termination with IP67 degree of protection, connected to 5-conductor

SWD4-..LR5.. round cable or directly to SmartWire-DT T-Connectors (IP67 I/O modules) Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz,

according to IEC/EN 61131-2, Vibrations Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall

(IEC/EN 60068-2-32) - max 0.3 m Mounting position As required Shock resistance 15 g, Mechanical, according to IEC/EN

60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max

55 °C Ambient storage temperature - min -40 °C Ambient storage temperature - ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-RC5-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.