

INDUSTRIAL COMPONENT DATA

SWD4-SFL8-12 174756 Y7-174756 EATON ELECTRIC Adapter SWDT, for conversion of flat cable 8 pole round connect..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-SFL8-12



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-SFL8-12
Catalog number	Y7-174756
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-D49E290E6A
Generated	2026-08-05

Product Overview

Adapter SWDT, for conversion of flat cable 8 pole round connector, 5-pole

SWD4-SFL8-12

Eaton SWD4 SWD switch cabinet bushing; 8 pole ribbon cable on 5-pin round cable

SmartWire-DT control panel cable gland for converting an 8-conductor ribbon cable to a 5-conductor round cable, separate 24 VDC, 4 A power supply for round cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Smartwire Darwin

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Switch cabinet bushing Catalog Number 174756 Model Code SWD4-SFL8-12 EAN 4015081712427 Product Length/Depth 82.4 mm Product Height 21 mm Product Width 35.2 mm Product Weight 0.045 kg

Certifications EN 50178

CSA File No.: 2324643

CSA

UL File No.: E29184

UL Category Control No.: NKCR

UL

IEC/EN 61131-2

CSA Class No.: 3211-07 General

Degree of protection IP20 (according to IEC/EN 60529, EN 50178, VBG 4)

IP20 Overvoltage category II Pollution degree 2 Product category SmartWire-DT accessories Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Drop and topple 50 mm Drop height, Drop to IEC/EN 60068-2-31 Height of fall (IEC/EN 60068-2-32) - max 0.3 m Mounting position As required Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Dry heat to IEC 60068-2-2

Damp heat, constant, to IEC 60068-2-3 Environmental conditions Condensation: prevent with appropriate measures Operating temperature - min -25 °C Operating temperature - max 70 °C Relative humidity 5 - 95 % (non-condensing, IEC/EN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-SFL8-12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.