

INDUSTRIAL COMPONENT DATA

SWD4-SP-4084 174705 Y7-174705 EATON ELECTRIC

SmartWire-DT splitter IP67, from M12 plug to two M8 sockets, 4-..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-SP-4084



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-SP-4084
Catalog number	Y7-174705
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-AC9D20CD6E
Generated	2026-08-06

Product Overview

SmartWire-DT splitter IP67, from M12 plug to two M8 sockets, 4-Pole, pin 4

SWD4-SP-4084

SmartWire-DT splitter with IP67 degree of protection, M12 plug into two 4 pole M8 sockets with I/O signal on pin 4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Smartwire Darwin
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Splitter Catalog Number 174705 Model Code SWD4-SP-4084 EAN 4015081711918

Product Length/Depth 47 mm Product Height 14.7 mm Product Width 31.4 mm Product Weight 0.03 kg Certifications CSA

UL Catalog Notes not relevant Features & Functions

Functions For splitting an M12 I/O connection's I/O signals General

Degree of protection IP67 (according to IEC/EN 60529, EN 50178, VBG 4)

IP67 Product category SmartWire-DT accessories Type Splitter with IP67 degree of protection, M12 plug into two 4 pole M8 sockets with I/O signal on pin 4 Ambient conditions, mechanical

Mounting position As required Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 90 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 90 °C Climatic proofing Damp heat,

constant, to IEC 60068-2-3

Dry heat to IEC 60068-2-2 Environmental conditions Condensation: permissible Operating temperature - min -25 °C

Operating temperature - max 90 °C Electrical rating

Power loss 0 W Communication

Connection to SmartWire-DT Yes Connection type 2 * M8 sockets, 4-pin, I/O on connection pin 4

Connection 1: M12 Plug (A-keyed) Design verification

Heat dissipation capacity P_{diss} 0 W Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance

Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclos...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-SP-4084 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.