

## INDUSTRIAL COMPONENT DATA

# SWIRE-CAB-008 107032 EATON ELECTRIC Connection cable, flush, SmartWire-DT, L 85mm

Brand: EATON - MOELLER | Manufacturer Part Number: SWIRE-CAB-008



|                 |                      |
|-----------------|----------------------|
| Manufacturer    | EATON - MOELLER      |
| MPN / Reference | SWIRE-CAB-008        |
| Catalog number  | 107032               |
| Category        | PLC connection cable |
| Minimum order   | 25 Pcs               |
| Document ID     | EO-EABED11B52        |
| Generated       | 2026-08-04           |

## Product Overview

Connection cable, flush, SmartWire-DT, L=85mm

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                 |
|--------------|-----------------|
| Catalog path | EATON - MOELLER |
|--------------|-----------------|

## Additional Product Information

Connection cable, flush, SmartWire-DT, L=85mm Eaton Catalog No. SWIRE-CAB-008 EL-Nummer (Norway) 4131954

SWIRE connecting cable, 6 pole, prefabricated with connectors at both ends, 8cm [ Delivery program

Basic function Connection system SmartWire Description Connection cable completely prefabricated Length 85 mm ,  
Technical data

Main conducting paths Rated impulse withstand voltage [Uimp] 6000 V AC Overvoltage category/pollution degree III/3

Rated operational voltage [Ue] 230 - 415 V Additional technical data Motor protective circuit breaker PKZM0, PKE PKZM0  
motor-protective circuit-breakers, see motor-protective circuit-breakers/PKZM0 product group

DILM contactors, see contactor product group

DILET timing relay, ETR, see contactors, electronic timing relays product group , Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per  
pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation,  
non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C

Operating ambient temperature max. +55 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts10.2.2

Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.1 Verification of  
thermal stability of enclosures Meets the product standard's requirements. 1...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWIRE-CAB-008 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.