

INDUSTRIAL COMPONENT DATA

SWD4-SML8-20 121381 Y7-121381 EATON ELECTRIC Switch cabinet bushing, SmartWire-DT, flat to round cable, plug

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-SML8-20



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-SML8-20
Catalog number	Y7-121381
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-A4130F75F5
Generated	2026-08-05

Product Overview

Switch cabinet bushing, SmartWire-DT, flat to round cable, plug

SWD4-SML8-20

SmartWire-DT switch cabinet bushing, transition from SWD ribbon cable to round cable, double conductor run pluggable, additional control voltage feeder is possible for the motor starter and contactor, suitable for wall thicknesses up to 4mm, degree of protection IP67, drilling dimensions 18.5mm, connection of SWD ribbon cable with blade terminal SWD4-8MF2 8 pole, connection round cable via plug

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Smartwire Darwin**

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Switch cabinet bushing Catalog Number 121381 Model Code SWD4-SML8-20 EAN 4015081192106 Product Length/Depth 21 mm Product Height 82.4 mm Product Width 35 mm Product Weight 0.05 kg

Certifications EN 50178

IEC/EN 61131-2

CSA

UL

UL File No.: E29184

CSA File No.: 2324643

CSA Class No.: 3211-07

UL Category Control No.: NKCR Catalog Notes not relevant General

Degree of protection IP20 (according to IEC/EN 60529, EN 50178, VBG 4)

IP20 Product category SmartWire-DT accessories Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Height of fall (IEC/EN 60068-2-32) - max 0.3 m Mounting position As required

Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-3

Dry heat to IEC 60068-2-2 Environmental conditions Condensation: prevent with appropriate measures Operating temperature - min -25 °C Operating temperature - max 70 °C Relative humidity 5 - 95 % (non-condensing, IEC/EN 60068-2-30) Electro magnetic compatibility

Air discharge 8 kV, according to IEC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-SML8-20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.