

## INDUSTRIAL COMPONENT DATA

# SWD4-SFL8-20 121380 Y7-121380 EATON ELECTRIC Switch cabinet bushing, SmartWire-DT, flat to round cable, sock..

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-SFL8-20



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | EATON - MOELLER                      |
| MPN / Reference | SWD4-SFL8-20                         |
| Catalog number  | Y7-121380                            |
| Category        | Accessories/spare parts for controls |
| Minimum order   | 1 Pcs                                |
| Document ID     | EO-388B09DFE9                        |
| Generated       | 2026-08-05                           |

## Product Overview

Switch cabinet bushing, SmartWire-DT, flat to round cable, socket  
SWD4-SFL8-20

SmartWire-DT switch cabinet bushing, transition from SWD ribbon cable to round cable, double conductor run pluggable, additional control voltage feeder is possible for the motor starter and contactor, suitable for wall thicknesses up to 4mm, degree of protection IP67, drilling dimensions 18.5mm, connection of SWD ribbon cable with blade terminal SWD4-8MF2 8 pole, connection round cable via socket

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                    |
|--------------|------------------------------------|
| Catalog path | EATON - MOELLER > Smartwire Darwin |
|--------------|------------------------------------|

## Additional Product Information

## General specifications

Product Name Eaton SWD4 Accessory Switch cabinet bushing Catalog Number 121380 Model Code SWD4-SFL8-20 EAN 4015081192090 Product Length/Depth 41 mm Product Height 83 mm Product Width 35 mm Product Weight 0.045 kg

Certifications UL File No.: E29184

EN 50178

CSA File No.: 2324643

UL

CSA

CSA Class No.: 3211-07

IEC/EN 61131-2

UL Category Control No.: NKCR General

Degree of protection IP20

IP20 (according to IEC/EN 60529, EN 50178, VBG 4) Product category SmartWire-DT accessories Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Height of fall (IEC/EN 60068-2-32) - max 0.3 m Mounting position As required

Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Dry heat to IEC 60068-2-2

Damp heat, constant, to IEC 60068-2-3 Environmental conditions Condensation: prevent with appropriate measures

Operating temperature - min -25 °C Operating temperature - max 70 °C Relative humidity 5 - 95 % (non-condensing, IEC/EN 60068-2-30) Electro magnetic compatibility

Air discharge 8 kV, according to IEC 61131-2, level 3, ESD Conta...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-SFL8-20 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.