

INDUSTRIAL COMPONENT DATA

**INX40N3-12W 150079 RES8133WSW0NMNN2MNDX EATON
ELECTRIC Switch-disconnector, 3p, 1250 A, withdrawable**

Brand: EATON - MOELLER | Manufacturer Part Number: INX40N3-12W



Manufacturer	EATON - MOELLER
MPN / Reference	INX40N3-12W
Catalog number	RES8133WSW0NMNN2MNDX
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-5D3050D4B1
Generated	2026-08-03

Product Overview

Switch-disconnector, 3p, 1250 A, withdrawable

INX switch-disconnector, acc. to IEC/EN 60947, optionally retrofittable with comprehensive accessories, any direction of incoming supply

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Switch-disconnector, 3p, 1250 A, withdrawable Eaton Catalog No. RES8133WSW0NMNN2MNDX INX switch-disconnector, acc. to IEC/EN 60947, optionally retrofittable with comprehensive accessories, any direction of incoming supply [Delivery program

Product range Air circuit-breakers/switch-disconnectors Product range Open switch-disconnectors Current Range Up to 4000 A Protective function without protection Installation type Withdrawable Cassette must be separately ordered. Construction size INX40 Release system without releases Standard/Approval IEC Number of poles 3 pole Degree of Protection IP20, IP55 with protective cover, IP41 door sealing frame optionally fittable by user with comprehensive accessories Rated current = rated uninterrupted current [In= Iu] 1200 A Rated short-circuit making capacity up to 440V/690V 42/42 [Icm] 187 kA Rated short-time withstand current t =1 s [Icw] 85 kA Rated short-time withstand current t =3 s [Icw] 66 kA , Technical data

General Standards IEC/EN 60947 Ambient temperatureStorage [?] -40 - +70 °C Ambient temperatureAmbient temperature -25 - +70 °C Mounting position Utilization category B Degree of Protection IP20, IP55 with protective cover, IP41 door sealing frame Direction of incoming supply as required Main conducting paths Rated current = rated uninterrupted current

[In= Iu] 1250 A Rated uninterrupted current at 50 °C [Iu] 1250 A Rated uninterrupted current at 60 °C [Iu] 1250 A Rated uninterrupted current at 70 °C [Iu] 1250 A Rated impulse wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / INX40N3-12W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.