


## INDUSTRIAL COMPONENT DATA

# DMV-250N/3 1814408 Y8-1814408 EATON ELECTRIC

## Switch-disconnector, 3 pole, 250 A, Without rotary handle and d..

Brand: EATON - MOELLER | Manufacturer Part Number: DMV-250N/3



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | DMV-250N/3          |
| Catalog number  | Y8-1814408          |
| Category        | Switch disconnector |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-4A3D7114E2       |
| Generated       | 2026-08-04          |

### Product Overview

Switch-disconnector, 3 pole, 250 A, Without rotary handle and drive shaft, surface mounting

DMV-250N/3

Eaton DMV Switch-disconnector, DMV, 250 A, 3 pole, Stop Function optional, Without rotary handle and drive shaft

Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMV, Stop Function: optional, Without rotary handle and drive shaft, Notes: visible contacts, Information about equipment supplied: auxiliary contact fitted by user., including connection materials, 3 pole, Degree of Protection: IP00, IP20 with terminal cover, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 147 kW, Rated uninterrupted current: I<sub>u</sub> = 250 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                               |
|--------------|-----------------------------------------------|
| Catalog path | EATON - MOELLER > DUMECO Switch-Disconnectors |
|--------------|-----------------------------------------------|

### Additional Product Information

General specifications

Product Name Eaton DMV Switch-disconnector Catalog Number 1814408 Model Code DMV-250N/3 EAN 8711426853812

Product Length/Depth 63 mm Product Height 135 mm Product Width 205 mm Product Weight 1.62 kg Certifications EAC

Lloyds

IEC/EN 60204

IEC/EN 60947-3

CE

RoHS

KEMA

IEC/EN 60947

VDE 0660 Features &amp; Functions

Features Version as emergency stop installation Functions Optional Stop Function Number of poles Three-pole General  
Accessories Actuator color Other Actuator type Other Degree of protection NEMA Other Degree of protection (front side)  
IP20 Lifespan, mechanical 10,000 Operations Mounting method Surface mounting Mounting position As required  
Overvoltage category III Pollution degree 3 Product Category Main switch

Switch-disconnector

Rated impulse withstand voltage (Uimp) 8000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1,  
table C.1 Suitable for Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min  
-30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 120 mm<sup>2</sup>, Flat conductor connection with busbars Screw size M8 x 20, Terminal screw Tightening torque  
14 Nm, Screw terminals Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) 2000 A Rated breaking capacity at 500 V (cos phi to IEC  
60947-3) 1760 A Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3) 11...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMV-250N/3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.