

INDUSTRIAL COMPONENT DATA

IN32S3-32F-1100V 123871 EATON ELECTRIC Int-Isolator, 3P, 3200A, 1100V, fixed

Brand: EATON - MOELLER | Manufacturer Part Number: IN32S3-32F-1100V



Manufacturer	EATON - MOELLER
MPN / Reference	IN32S3-32F-1100V
Catalog number	123871
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-6355C4924D
Generated	2026-08-05

Product Overview

Int-Isolator, 3P, 3200A, 1100V, fixed

Switch-disconnector, Air circuit-breakers/switch-disconnectors, Open switch-disconnectors for 1100 V AC, 4000 to 6300 A, without protection, Fixed, Construction size: IN32S, Standard/Approval: IEC, Number of poles: 3 pole, Degree of Protection: IP20, IP55 with protective cover, Rated current = rated uninterrupted current: $I_n = I_u$ 3200 A, up to 440 V 50/60 Hz: I_{cm} 210 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

Delivery programme Product range Air circuit-breakers/switch-disconnectors

Product range Open switch-disconnectors for 1100 V AC

Current Range over 4000 A

Protective function Switch disconnecter

Installation type Fixed

Construction size IN32S

Release system Electronic release

Standard/Approval IEC

Number of poles 3 pole

Degree of Protection IP20, IP55 with protective cover

Rated current = rated uninterrupted current $I_n = I_u$ A 3200

Making capacity Icm to 440 V 50/60 Hz Icm kA 210

Notes Including rear connection main terminals and secondary terminal blocks according to ordered breaker options.

Technical data General

Standards IEC/EN 60947

Ambient temperature

Storage ? °C -40 - +70

Operating (open) °C -25 - +70

Mounting position >>

Utilization category B

Degree of Protection IP20, IP55 with protective cover

Direction of incoming supply as required

Main conducting paths

Rated current = rated uninterrupted current In= Iu A 3200

Rated uninterrupted current at 50 °C Iu A 3100

Rated uninterrupted current at 60 °C Iu A 2800

Rated uninterrupted current at 70 °C Iu A 2550

Rated impulse withstand voltage Uimp V AC 8000

Rated operational voltage Ue V AC 690

Use in IT electrical power networks up to U = 440 V IIT kA 39

Overvoltage category/pollution degree III/3

Rated insulation voltage Ui V 1100

Switching capacity

Rated short-circuit making capacity Icm

up to 440 V 50/60 Hz Icm kA 210

up to 690 V 50/60 Hz Icm kA 53

Operating times

Closing delay via spring release ms 35

Break times ms 40

T...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IN32S3-32F-1100V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.