

INDUSTRIAL COMPONENT DATA

IN63H3-40W 124226 EATON ELECTRIC Switch-disconnector, 3p, 4000A, withdrawable part

Brand: EATON - MOELLER | Manufacturer Part Number: IN63H3-40W



Manufacturer	EATON - MOELLER
MPN / Reference	IN63H3-40W
Catalog number	124226
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-2951A65B3A
Generated	2026-08-03

Product Overview

Switch-disconnector, 3p, 4000A, withdrawable part

Switch-disconnector, Air circuit-breakers/switch-disconnectors, Open switch-disconnectors, 4000 to 6300 A, without protection, Withdrawable, Construction size: IN63, Standard/Approval: IEC, Number of poles: 3 pole, Degree of Protection: IP20, IP55 with protective cover, Rated current = rated uninterrupted current: $I_n = I_u$ 4000 A, up to 440 V 50/60 Hz: I_{cm} 138 kA, $t = 1$ s: I_{cw} 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

Additional Product Information

Delivery programme Product range Air circuit-breakers/switch-disconnectors

Product range Open switch-disconnectors

Current Range over 4000 A

Protective function Switch disconnector

Installation type Withdrawable

Construction size IN63

Release system Electronic release

Standard/Approval IEC

Number of poles 3 pole

Degree of Protection IP20, IP55 with protective cover

Rated current = rated uninterrupted current $I_n = I_u$ A 4000

Making capacity Icm to 440 V 50/60 Hz Icm kA 138

t = 1 s Icw kA 100

t = 3 s Icw kA 65

Notes Including rear connection main terminals and secondary terminal blocks according to ordered breaker options.

Note concerning the product Cassette needs to be ordered separately.

Technical data General

Standards IEC/EN 60947

Ambient temperature

Storage ? °C -40 - +70

Operating (open) °C -25 - +70

Mounting position >>

Utilization category B

Degree of Protection IP20, IP55 with protective cover

Direction of incoming supply as required

Main conducting paths

Rated current = rated uninterrupted current In= Iu A 4000

Rated uninterrupted current at 50 °C Iu A 4000

Rated uninterrupted current at 60 °C Iu A 4000

Rated uninterrupted current at 70 °C Iu A 4000

Rated impulse withstand voltage Uimp V AC 8000

Rated operational voltage Ue V AC 690

Use in IT electrical power networks up to U = 440 V IIT kA 88888888

Overvoltage category/pollution degree III/3

Rated insulation voltage Ui V 1000

Switching capacity

Rated short-circuit making capacity Icm

up to 440 V 50/60 Hz Icm kA 138....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IN63H3-40W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.