

INDUSTRIAL COMPONENT DATA

IN63N3-63F 124318 Y7-124318 EATON ELECTRIC

Switch-disconnector, 3p, 6300A, fixed

Brand: EATON - MOELLER | Manufacturer Part Number: IN63N3-63F



Manufacturer	EATON - MOELLER
MPN / Reference	IN63N3-63F
Catalog number	Y7-124318
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-4359829A51
Generated	2026-08-03

Product Overview

Switch-disconnector, 3p, 6300A, fixed

Switch-disconnector, Air circuit-breakers/switch-disconnectors, Open switch-disconnectors, 4000 to 6300 A, without protection, Fixed, Construction size: IN63, Standard/Approval: IEC, Number of poles: 3 pole, Degree of Protection: IP20, IP55 with protective cover, Rated current = rated uninterrupted current: $I_n = I_u$ 6300 A, up to 440 V 50/60 Hz: I_{cm} 217 kA, $t = 1$ s: I_{cw} 85 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

Additional Product Information

Switch-disconnector, 3p, 6300A, fixed Switch-disconnector, Air circuit-breakers/switch-disconnectors, Open switch-disconnectors, 4000 to 6300 A, without protection, Fixed, Construction size: IN63, Standard/Approval: IEC, Number of poles: 3 pole, Degree of Protection: IP20, IP55 with protective cover, Rated current = rated uninterrupted current: $I_n = I_u$ 6300 A, up to 440 V 50/60 Hz: I_{cm} 217 kA, $t = 1$ s: I_{cw} 85 kA [Delivery program

Product range Air circuit-breakers/switch-disconnectors Product range Open switch-disconnectors Current Range 4000 to 6300 A Protective function without protection Installation type Fixed Construction size IN63 Standard/Approval IEC Number of poles 3 pole Degree of Protection IP20, IP55 with protective cover Rated current = rated uninterrupted current [$I_n = I_u$] 6300 A up to 440 V 50/60 Hz [I_{cm}] 217 kA $t = 1$ s [I_{cw}] 85 kA Notes Including rear connection main terminals and secondary terminal blocks according to ordered breaker options.

, Technical data

General Standards IEC/EN 60947 Ambient temperatureStorage [?] -40 - +70 °C Ambient temperatureOperating (open) -25 -

+70 °C Mounting position Utilization category B Degree of Protection IP20, IP55 with protective cover Direction of incoming supply as required Main conducting paths Rated current = rated uninterrupted current [In= Iu] 6300 A Rated uninterrupted current at 50 °C [Iu] 6200 A Rated uninterrupted current at 60 °C [Iu] 5600 A Rated uninterrupted current at 70 °C [Iu] 5100 A Rated impulse withs...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IN63N3-63F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.