

INDUSTRIAL COMPONENT DATA

IN20B3-08F 123424 EATON ELECTRIC Switch-disconnector, 3p, 800A, fixed

Brand: EATON - MOELLER | Manufacturer Part Number: IN20B3-08F



Manufacturer	EATON - MOELLER
MPN / Reference	IN20B3-08F
Catalog number	123424
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-6029E31314
Generated	2026-08-04

Product Overview

Switch-disconnector, 3p, 800A, fixed

Switch-disconnector, Air circuit-breakers/switch-disconnectors, Open switch-disconnectors, 4000 to 6300 A, without protection, Fixed, Construction size: IN20, Standard/Approval: IEC, Number of poles: 3 pole, Degree of Protection: IP20, IP55 with protective cover, Rated current = rated uninterrupted current: In = Iu 800 A, up to 440 V 50/60 Hz: Icm 55 kA, t = 1 s: Icw 50 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER

Additional Product Information

ETIM for 123424 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

false

Version as maintenance-/service switch (EF006986)

false

Version as safety switch (EF006985)

false

Version as emergency stop installation (EF006959)

false

Version as reversing switch (EF009408)
false
Number of switches (EF005586)
Max. rated operation voltage Ue AC (EF007355)
None V
Rated operating voltage (EF001435)
None V
Rated permanent current Iu (EF001389)
None A
Rated permanent current at AC-23, 400 V (EF011777)
None A
Rated permanent current at AC-21, 400 V (EF009165)
None A
Rated operation power at AC-3, 400 V (EF001364)
None kW
Rated short-time withstand current Icw (EF007050)
None kA
Rated operation power at AC-23, 400 V (EF007027)
None kW
Switching power at 400 V (EF009166)
None kW
Conditioned rated short-circuit current Iq (EF001444)
None kA
Number of poles (EF001391)
3
Number of auxiliary contacts as normally closed contact (EF001377)
Number of auxiliary contacts as normally open contact (EF001376)
Number of auxiliary contacts as change-over contact (EF003531)
Motor drive optional (EF007386)
false
Motor drive integrated (EF006697)
false
Voltage release optional (EF007491)
false
Device construction (EF008240)
Suitable for front mounting 4-hole (EF007247)
false
Suitable for front mounting centre (EF007248)
false
Suitable for distribution board installation (EF007262)
false
Suitable for intermediate mounting (EF007264)
false
Col...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IN20B3-08F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.