

INDUSTRIAL COMPONENT DATA

DMM-125/1-SK 1314203 Y8-1314203 EATON ELECTRIC Switch-disconnector, 3 pole + N, 125 A, Without rotary handle..

Brand: EATON - MOELLER | Manufacturer Part Number: DMM-125/1-SK



Manufacturer	EATON - MOELLER
MPN / Reference	DMM-125/1-SK
Catalog number	Y8-1314203
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-EB44E223A9
Generated	2026-08-04

Product Overview

Switch-disconnector, 3 pole + N, 125 A, Without rotary handle and drive shaft, surface mounting, Vertical connection
DMM-125/1-SK

Eaton DMM Switch-disconnector, DMM, 125 A, 3P + N (solid), Stop Function optional, Without rotary handle and drive shaft, Vertical connection

Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMM, Stop Function: optional, Without rotary handle and drive shaft, Information about equipment supplied: auxiliary contact fitted by user., 3 pole + SN (direct), Degree of Protection: IP20, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 59 kW, Rated uninterrupted current: I_u = 125 A, Connection technique: Vertical connection, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DMM Switch-disconnector Catalog Number 1314203 Model Code DMM-125/1-SK EAN

8711426691346 Product Length/Depth 152 mm Product Height 108 mm Product Width 132 mm Product Weight 0.9 kg

Certifications KEMA

RoHS

IEC/EN 60204

IEC/EN 60947

Lloyds

EAC

CE

VDE 0660

IEC/EN 60947-3 Features & Functions

Features Version as main switch

Version as maintenance-/service switch Functions Optional Stop Function Number of poles Three-pole + N General Accessories Auxiliary contact fitted by user. Actuator color Other Actuator type Other Connection type Vertical Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 10,000 Operations Mounting method Surface mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Distribution board installation

Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 6 - 70 mm², flexible with ferrules to DIN 46228 Stripping length (main cable) 21 mm Tightening torque 7 Nm, Screw terminals Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) 480 A Rated breaking capacity at 500 V (cos phi....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMM-125/1-SK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.