

INDUSTRIAL COMPONENT DATA

DMV-1250N/4 1814592 Y8-1814592 EATON ELECTRIC

Switch-disconnector, 4 pole, 1250 A, Without rotary handle and..

Brand: EATON - MOELLER | Manufacturer Part Number: DMV-1250N/4



Manufacturer	EATON - MOELLER
MPN / Reference	DMV-1250N/4
Catalog number	Y8-1814592
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-D8EE41820E
Generated	2026-08-06

Product Overview

Switch-disconnector, 4 pole, 1250 A, Without rotary handle and drive shaft, surface mounting

DMV-1250N/4

Eaton DMV Switch-disconnector, DMV, 1250 A, 4 pole, Stop Function optional, Without rotary handle and drive shaft

Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMV, Stop Function: optional, Without rotary handle and drive shaft, Notes: visible contacts, Information about equipment supplied: auxiliary contact fitted by user., including connection materials, 4 pole, Degree of Protection: IP00, IP20 with terminal cover, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 750 kW, Rated uninterrupted current: $I_u = 1250$ A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DMV Switch-disconnector Catalog Number 1814592 Model Code DMV-1250N/4 EAN

8711426640481 Product Length/Depth 116 mm Product Height 290 mm Product Width 385 mm Product Weight 13.245 kg

Certifications IEC/EN 60204

EAC

KEMA

Lloyds

RoHS

CE

VDE 0660

IEC/EN 60947

IEC/EN 60947-3 Features & Functions

Features Version as main switch

Version as maintenance-/service switch

Version as emergency stop installation Functions Optional Stop Function Number of poles Four-pole General

Accessories Actuator color Other Actuator type Other Degree of protection NEMA Other Degree of protection (front side)

IP20 Lifespan, mechanical 5,000 Operations Mounting method Surface mounting Mounting position As required

Overvoltage category III Pollution degree 3 Product Category Main switch

Switch-disconnector

Rated impulse withstand voltage (Uimp) 12000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Distribution board installation

Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 800 mm², Flat conductor connection with busbars Screw size M16 x 50, Terminal screw Tightening torque 60 Nm, Screw terminals Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) 10000 A Rated breaking capacity at 500...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMV-1250N/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.