

INDUSTRIAL COMPONENT DATA

DMM-125/4 1314211 Y8-1314211 EATON ELECTRIC

Switch-disconnector, 4 pole, 125 A, With black rotary handle and..

Brand: EATON - MOELLER | Manufacturer Part Number: DMM-125/4



Manufacturer	EATON - MOELLER
MPN / Reference	DMM-125/4
Catalog number	Y8-1314211
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-64D880BC37
Generated	2026-08-04

Product Overview

Switch-disconnector, 4 pole, 125 A, With black rotary handle and drive shaft, surface mounting, Vertical connection
DMM-125/4

Eaton DMM Switch-disconnector, DMM, 125 A, 4 pole, With black rotary handle and drive shaft, Vertical connection
Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMM,
With black rotary handle and drive shaft, Information about equipment supplied: auxiliary contact fitted by user., 4 pole,
Notes: 1 padlock, 5 mm, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP20, Design: surface
mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 59 kW, Rated uninterrupted current: I_u = 125 A, Connection
technique: Vertical connection, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to
IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton DMM Switch-disconnector Catalog Number 1314211 Model Code DMM-125/4 EAN 8711426911871
Product Length/Depth 152 mm Product Height 108 mm Product Width 132 mm Product Weight 0.907 kg Certifications CE
Lloyds
IEC/EN 60947

KEMA

IEC/EN 60947-3

IEC/EN 60204

VDE 0660

RoHS

EAC Features & Functions

Features Version as maintenance-/service switch

Version as main switch Fitted with: Black rotary handle and drive shaft Locking facility Lockable in the 0 (Off) position

Number of poles Four-pole General

Accessories Auxiliary contact fitted by user. Actuator color Black Actuator type Short thumb-grip Connection type Vertical

Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 10,000 Operations Mounting

method Surface mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category

Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Distribution board installation

Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 6 - 70 mm², flexible with ferrules to DIN 46228 Stripping length (main cable) 21 mm Tightening torque 7 Nm, Screw terminals Electrical rating

Rated breaking capacity at 400/415 V (c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMM-125/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.