

INDUSTRIAL COMPONENT DATA

DMM-125/4+CM 1314207 Y8-1314207 EATON ELECTRIC

Switch-disconnector, 4 pole, 125 A, With blue rotary handle (..

Brand: EATON - MOELLER | Manufacturer Part Number: DMM-125/4+CM



Manufacturer	EATON - MOELLER
MPN / Reference	DMM-125/4+CM
Catalog number	Y8-1314207
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-2AD6C23893
Generated	2026-08-02

Product Overview

Switch-disconnector, 4 pole, 125 A, With blue rotary handle (Type C) and drive shaft, flush mounting, Vertical connection DMM-125/4+CM

Eaton DMM Switch-disconnector, DMM, 125 A, 4 pole, With blue rotary handle (Type C) and drive shaft, Vertical connection Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMM, With blue rotary handle (Type C) and drive shaft, Information about equipment supplied: auxiliary contact fitted by user., 4 pole, Notes: 1 padlock, 5 mm, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP20, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 59 kW, Rated uninterrupted current: I_u = 125 A, Connection technique: Vertical connection, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DMM Switch-disconnector Catalog Number 1314207 Model Code DMM-125/4+CM EAN

8711426752757 Product Length/Depth 152 mm Product Height 108 mm Product Width 132 mm Product Weight 1.04 kg

Certifications RoHS

CE

EAC

IEC/EN 60947-3

KEMA

Lloyds

VDE 0660

IEC/EN 60204

IEC/EN 60947 Features & Functions

Features Version as maintenance-/service switch

Version as main switch Fitted with: Blue rotary handle (Type C) and drive shaft Locking facility Lockable in the 0 (Off) position Number of poles Four-pole General

Accessories Auxiliary contact fitted by user. Actuator color Other Actuator type Short thumb-grip Connection type Vertical Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 10,000 Operations Mounting method Flush mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table

C.1 Suitable for Ground mounting

Intermediate mounting

Distribution board installation Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 6 - 70 mm², flexible with ferrules to DIN 46228 Stripping length (main cable) 21 mm Tightening torque 7 Nm, Screw terminals Electrical rating

Rated bre...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMM-125/4+CM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.