

INDUSTRIAL COMPONENT DATA

IN32S4-32W-1100V 123872 EATON ELECTRIC Int-Isolator, 4P, 3200A, 1100V, removable without chassis

Brand: EATON - MOELLER | Manufacturer Part Number: IN32S4-32W-1100V



Manufacturer	EATON - MOELLER
MPN / Reference	IN32S4-32W-1100V
Catalog number	123872
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-015F8A13B1
Generated	2026-08-04

Product Overview

Int-Isolator, 4P, 3200A, 1100V, removable without chassis

Switch-disconnector, Air circuit-breakers/switch-disconnectors, Open switch-disconnectors for 1100 V AC, 4000 to 6300 A, without protection, Withdrawable, Construction size: IN32S, Standard/Approval: IEC, Number of poles: 4 pole, Degree of Protection: IP20, IP55 with protective cover, Rated current = rated uninterrupted current: $I_n = I_u$ 3200 A, up to 440 V 50/60 Hz: I_{cm} 210 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

Additional Product Information

Delivery programme Product range Air circuit-breakers/switch-disconnectors

Product range Open switch-disconnectors for 1100 V AC

Current Range over 4000 A

Protective function Switch disconnecter

Installation type Withdrawable

Construction size IN32S

Release system Electronic release

Standard/Approval IEC

Number of poles 4 pole

Degree of Protection IP20, IP55 with protective cover

Rated current = rated uninterrupted current $I_n = I_u$ A 3200

Making capacity Icm to 440 V 50/60 Hz Icm kA 210

Notes Including rear connection main terminals and secondary terminal blocks according to ordered breaker options.

Note concerning the product Cassette needs to be ordered separately.

Technical data General

Standards IEC/EN 60947

Ambient temperature

Storage ? °C -40 - +70

Operating (open) °C -25 - +70

Mounting position >>

Utilization category B

Degree of Protection IP20, IP55 with protective cover

Direction of incoming supply as required

Main conducting paths

Rated current = rated uninterrupted current In= Iu A 3200

Rated uninterrupted current at 50 °C Iu A 3100

Rated uninterrupted current at 60 °C Iu A 2800

Rated uninterrupted current at 70 °C Iu A 2550

Rated impulse withstand voltage Uimp V AC 8000

Rated operational voltage Ue V AC 690

Use in IT electrical power networks up to U = 440 V IIT kA 39

Overvoltage category/pollution degree III/3

Rated insulation voltage Ui V 1100

Switching capacity

Rated short-circuit making capacity Icm

up to 440 V 50/60 Hz Icm kA 210

up to 690 V 50/60 Hz Icm kA....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IN32S4-32W-1100V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.