

INDUSTRIAL COMPONENT DATA

DCM-40/4-SK+FM 1314113 Y8-1314113 EATON ELECTRIC

Switch-disconnector, 4 pole, 40 A, Without rotary handle an..

Brand: EATON - MOELLER | Manufacturer Part Number: DCM-40/4-SK+FM



Manufacturer	EATON - MOELLER
MPN / Reference	DCM-40/4-SK+FM
Catalog number	Y8-1314113
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-C1B96886EE
Generated	2026-08-03

Product Overview

Switch-disconnector, 4 pole, 40 A, Without rotary handle and drive shaft, surface mounting, Rear connection; for front connection ? 1314344

DCM-40/4-SK+FM

Eaton DCM Switch-disconnector, DCM, 40 A, 4 pole, Stop Function optional, Without rotary handle and drive shaft, Rear connection; for front connection ? 1314344

Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DCM, Stop Function: optional, Without rotary handle and drive shaft, Notes: Rear connection; for front connection ? 1314344, 4 pole, Degree of Protection: IP20, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 20 kW, Rated uninterrupted current: I_u = 40 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton DCM Switch-disconnector Catalog Number 1314113 Model Code DCM-40/4-SK+FM EAN 8711426355774 Product Length/Depth 146 mm Product Height 74 mm Product Width 84 mm Product Weight 0.5 kg

Certifications EAC

CE

RoHS

IEC/EN 60947

KEMA

Lloyds

IEC/EN 60947-3

IEC/EN 60204

VDE 0660 Features & Functions

Functions Optional Stop Function Number of poles Four-pole General

Actuator color Other Actuator type Other Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 10,000 Operations Mounting method Surface mounting Mounting position As required Overvoltage category III

Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1)

B10d values as per EN ISO 13849-1, table C.1 Suitable for Ground mounting

Distribution board installation Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 2.5 - 16 mm², solid

1.5 - 25 mm², flexible Stripping length (main cable) 14 mm Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) 320 A Rated insulation voltage (Ui) 690 V Rated operational current (Ie) at AC-21, 400 V, 415 V 40 A Rated operational current (Ie) at AC-22, 380 V, 400 V, 415 V 40 A Rated operational current (Ie) at AC-23A, 400 V, 415 V 40 A Rated operati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DCM-40/4-SK+FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.