

INDUSTRIAL COMPONENT DATA

DMM-40/4-SK 1314053 Y8-1314053 EATON ELECTRIC

Switch-disconnector, 4 pole, 40 A, Without rotary handle and d..

Brand: EATON - MOELLER | Manufacturer Part Number: DMM-40/4-SK



Manufacturer	EATON - MOELLER
MPN / Reference	DMM-40/4-SK
Catalog number	Y8-1314053
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-EE9EFB1EB3
Generated	2026-08-04

Product Overview

Switch-disconnector, 4 pole, 40 A, Without rotary handle and drive shaft, surface mounting, Vertical connection
DMM-40/4-SK

Eaton DMM Switch-disconnector, DMM, 40 A, 4 pole, Stop Function optional, Without rotary handle and drive shaft, Vertical connection

Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMM, Stop Function: optional, Without rotary handle and drive shaft, Information about equipment supplied: auxiliary contact fitted by user., 4 pole, Degree of Protection: IP20, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 22 kW, Rated uninterrupted current: I_u = 40 A, Connection technique: Vertical connection, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton DMM Switch-disconnector Catalog Number 1314053 Model Code DMM-40/4-SK EAN 8711426761742 Product Length/Depth 146 mm Product Height 74 mm Product Width 84 mm Product Weight 0.61 kg
Certifications IEC/EN 60947-3
EAC

CE

KEMA

RoHS

IEC/EN 60947

VDE 0660

IEC/EN 60204

Lloyds Features & Functions

Features Version as maintenance-/service switch

Version as main switch Functions Optional Stop Function Number of poles Four-pole General

Accessories Auxiliary contact fitted by user. Actuator color Other Actuator type Other Connection type Vertical Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 8,500 Operations Mounting method Surface mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Ground mounting

Distribution board installation Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 1.5 - 25 mm², flexible with ferrules to DIN 46228

2.5 - 16 mm², solid Stripping length (main cable) 14 mm Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) 320 A Rated breaking capacity at 500 V (cos phi to IEC 60947-3) 264 A Rate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMM-40/4-SK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.