

INDUSTRIAL COMPONENT DATA

IN63H4-50F 124392 Y7-124392 EATON ELECTRIC

Switch-disconnector, 4p, 5000A, fixed

Brand: EATON - MOELLER | Manufacturer Part Number: IN63H4-50F



Manufacturer	EATON - MOELLER
MPN / Reference	IN63H4-50F
Catalog number	Y7-124392
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-6E7C355FE0
Generated	2026-08-01

Product Overview

Switch-disconnector, 4p, 5000A, fixed

Switch-disconnector, Air circuit-breakers/switch-disconnectors, Open switch-disconnectors, 4000 to 6300 A, without protection, Fixed, Construction size: IN63, Standard/Approval: IEC, Number of poles: 4 pole, Degree of Protection: IP20, IP55 with protective cover, Rated current = rated uninterrupted current: $I_n = I_u$ 5000 A, up to 440 V 50/60 Hz: I_{cm} 217 kA, $t = 1$ s: I_{cw} 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

Additional Product Information

Switch-disconnector, 4p, 5000A, fixed Switch-disconnector, Air circuit-breakers/switch-disconnectors, Open switch-disconnectors, 4000 to 6300 A, without protection, Fixed, Construction size: IN63, Standard/Approval: IEC, Number of poles: 4 pole, Degree of Protection: IP20, IP55 with protective cover, Rated current = rated uninterrupted current: $I_n = I_u$ 5000 A, up to 440 V 50/60 Hz: I_{cm} 217 kA, $t = 1$ s: I_{cw} 100 kA [Delivery program

Product range Air circuit-breakers/switch-disconnectors Product range Open switch-disconnectors Current Range 4000 to 6300 A Protective function without protection Installation type Fixed Construction size IN63 Standard/Approval IEC Number of poles 4 pole Degree of Protection IP20, IP55 with protective cover Rated current = rated uninterrupted current [$I_n = I_u$] 5000 A up to 440 V 50/60 Hz [I_{cm}] 217 kA $t = 1$ s [I_{cw}] 100 kA Notes Including rear connection main terminals and secondary terminal blocks according to ordered breaker options.

, Technical data

General Standards IEC/EN 60947 Ambient temperatureStorage [?] -40 - +70 °C Ambient temperatureOperating (open) -25 -

+70 °C Mounting position Utilization category B Degree of Protection IP20, IP55 with protective cover Direction of incoming supply as required Main conducting paths Rated current = rated uninterrupted current [$I_n = I_u$] 5000 A Rated uninterrupted current at 50 °C [I_u] 5000 A Rated uninterrupted current at 60 °C [I_u] 5000 A Rated uninterrupted current at 70 °C [I_u] 5000 A Rated impulse wit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IN63H4-50F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.