

**INDUSTRIAL COMPONENT DATA**

# IN63N4-63F 124373 Y7-124373 EATON ELECTRIC

## Switch-disconnector, 4p, 6300A, fixed

Brand: EATON - MOELLER | Manufacturer Part Number: IN63N4-63F



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | IN63N4-63F          |
| Catalog number  | Y7-124373           |
| Category        | Switch disconnector |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-3D99CEA139       |
| Generated       | 2026-08-02          |

### Product Overview

Switch-disconnector, 4p, 6300A, fixed

Switch-disconnector, Air circuit-breakers/switch-disconnectors, Open switch-disconnectors, 4000 to 6300 A, without protection, Fixed, Construction size: IN63, Standard/Approval: IEC, Number of poles: 4 pole, Degree of Protection: IP20, IP55 with protective cover, Rated current = rated uninterrupted current:  $I_n = I_u$  6300 A, up to 440 V 50/60 Hz:  $I_{cm}$  217 kA,  $t = 1$  s:  $I_{cw}$  85 kA

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

### Additional Product Information

Switch-disconnector, 4p, 6300A, fixed Switch-disconnector, Air circuit-breakers/switch-disconnectors, Open switch-disconnectors, 4000 to 6300 A, without protection, Fixed, Construction size: IN63, Standard/Approval: IEC, Number of poles: 4 pole, Degree of Protection: IP20, IP55 with protective cover, Rated current = rated uninterrupted current:  $I_n = I_u$  6300 A, up to 440 V 50/60 Hz:  $I_{cm}$  217 kA,  $t = 1$  s:  $I_{cw}$  85 kA [ Delivery program

Product range Air circuit-breakers/switch-disconnectors Product range Open switch-disconnectors Current Range 4000 to 6300 A Protective function without protection Installation type Fixed Construction size IN63 Standard/Approval IEC Number of poles 4 pole Degree of Protection IP20, IP55 with protective cover Rated current = rated uninterrupted current [ $I_n = I_u$ ] 6300 A up to 440 V 50/60 Hz [ $I_{cm}$ ] 217 kA  $t = 1$  s [ $I_{cw}$ ] 85 kA Notes Including rear connection main terminals and secondary terminal blocks according to ordered breaker options.

, Technical data

General Standards IEC/EN 60947 Ambient temperatureStorage [?] -40 - +70 °C Ambient temperatureOperating (open) -25 -

+70 °C Mounting position Utilization category B Degree of Protection IP20, IP55 with protective cover Direction of incoming supply as required Main conducting paths Rated current = rated uninterrupted current [In= Iu] 6300 A Rated uninterrupted current at 50 °C [Iu] 6200 A Rated uninterrupted current at 60 °C [Iu] 5600 A Rated uninterrupted current at 70 °C [Iu] 5100 A Rated impulse withs...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IN63N4-63F with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.