

## INDUSTRIAL COMPONENT DATA

# DCM-63/4+CM 1314007 Y8-1314007 EATON ELECTRIC

## Switch-disconnector, 4 pole, 63 A, With blue rotary handle and..

Brand: EATON - MOELLER | Manufacturer Part Number: DCM-63/4+CM



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | DCM-63/4+CM         |
| Catalog number  | Y8-1314007          |
| Category        | Switch disconnector |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-970C9F0DDF       |
| Generated       | 2026-08-02          |

### Product Overview

Switch-disconnector, 4 pole, 63 A, With blue rotary handle and drive shaft, flush mounting, Vertical connection  
DCM-63/4+CM

Eaton DCM Switch-disconnector, DCM, 63 A, 4 pole, With blue rotary handle and drive shaft, Vertical connection

Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DCM, With blue rotary handle and drive shaft, 4 pole, Notes: 1 padlock, 5 mm, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP20, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I<sub>u</sub> = 63 A, Connection technique: Vertical connection, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                               |
|--------------|-----------------------------------------------|
| Catalog path | EATON - MOELLER > DUMECO Switch-Disconnectors |
|--------------|-----------------------------------------------|

### Additional Product Information

General specifications

Product Name Eaton DCM Switch-disconnector Catalog Number 1314007 Model Code DCM-63/4+CM EAN

8711426215078 Product Length/Depth 146 mm Product Height 74 mm Product Width 84 mm Product Weight 0.58 kg

Certifications IEC/EN 60204

IEC/EN 60947

KEMA

VDE 0660

CE

RoHS

EAC

IEC/EN 60947-3

Lloyds Features & Functions

Features Version as main switch

Version as maintenance-/service switch Fitted with: Blue rotary handle and drive shaft Locking facility Lockable in the 0 (Off) position Number of poles Four-pole General

Actuator color Other Actuator type Short thumb-grip Connection type Vertical Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 10,000 Operations Mounting method Flush mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Distribution board installation

Intermediate mounting

Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 2.5 - 16 mm<sup>2</sup>, solid

1.5 - 25 mm<sup>2</sup>, flexible Stripping length (main cable) 14 mm Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) 504 A Rated insulation voltage (Ui) 690 V Rated op...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DCM-63/4+CM with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.