

INDUSTRIAL COMPONENT DATA

DMM-63/4 1314162 Y8-1314162 EATON ELECTRIC

Switch-disconnector, 4 pole, 63 A, With black rotary handle and d..

Brand: EATON - MOELLER | Manufacturer Part Number: DMM-63/4



Manufacturer	EATON - MOELLER
MPN / Reference	DMM-63/4
Catalog number	Y8-1314162
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-23C4DB4433
Generated	2026-08-04

Product Overview

Switch-disconnector, 4 pole, 63 A, With black rotary handle and drive shaft, surface mounting, Vertical connection
DMM-63/4

Eaton DMM Switch-disconnector, DMM, 63 A, 4 pole, With black rotary handle and drive shaft, Vertical connection
Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMM,
With black rotary handle and drive shaft, Information about equipment supplied: auxiliary contact fitted by user., 4 pole,
Notes: 1 padlock, 5 mm, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP20, Design: surface
mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, Connection
technique: Vertical connection, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to
IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton DMM Switch-disconnector Catalog Number 1314162 Model Code DMM-63/4 EAN 8711426625006
Product Length/Depth 146 mm Product Height 74 mm Product Width 84 mm Product Weight 0.62 kg Certifications IEC/EN
60204
IEC/EN 60947-3

VDE 0660

EAC

IEC/EN 60947

KEMA

RoHS

CE

Lloyds Features & Functions

Features Version as main switch

Version as maintenance-/service switch Fitted with: Black rotary handle and drive shaft Locking facility Lockable in the 0 (Off) position Number of poles Four-pole General

Accessories Auxiliary contact fitted by user. Actuator color Black Actuator type Short thumb-grip Connection type Vertical Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 8,500 Operations Mounting method Surface mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Ground mounting

Distribution board installation Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 1.5 - 25 mm², flexible with ferrules to DIN 46228

2.5 - 16 mm², solid Stripping length (main cable) 14 mm Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMM-63/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.