

INDUSTRIAL COMPONENT DATA

DMM-63/4+SK 1314160 Y8-1314160 EATON ELECTRIC

Switch-disconnector, 4 pole, 63 A, With blue rotary handle (Ty..

Brand: EATON - MOELLER | Manufacturer Part Number: DMM-63/4+SK



Manufacturer	EATON - MOELLER
MPN / Reference	DMM-63/4+SK
Catalog number	Y8-1314160
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-854D7A81F3
Generated	2026-08-04

Product Overview

Switch-disconnector, 4 pole, 63 A, With blue rotary handle (Type C) and drive shaft, flush mounting, Vertical connection DMM-63/4+SK

Eaton DMM Switch-disconnector, DMM, 63 A, 4 pole, With blue rotary handle (Type C) and drive shaft, Vertical connection Switch-disconnector, Product range: Switch-disconnector, Main switch, maintenance switch, Part group reference: DMM, With blue rotary handle (Type C) and drive shaft, Information about equipment supplied: auxiliary contact fitted by user., 4 pole, Notes: 1 padlock, 5 mm, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: IP20, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, Connection technique: Vertical connection, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton DMM Switch-disconnector Catalog Number 1314160 Model Code DMM-63/4+SK EAN 8711426431652 Product Length/Depth 146 mm Product Height 74 mm Product Width 84 mm Product Weight 0.69 kg
Certifications Lloyds
IEC/EN 60947-3

CE

KEMA

VDE 0660

RoHS

IEC/EN 60947

EAC

IEC/EN 60204 Features & Functions

Features Version as main switch

Version as maintenance-/service switch Fitted with: Blue rotary handle (Type C) and drive shaft Locking facility Lockable in the 0 (Off) position Number of poles Four-pole General

Accessories Auxiliary contact fitted by user. Actuator color Other Actuator type Short thumb-grip Connection type Vertical Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 8,500 Operations Mounting method Rear mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1 Suitable for Distribution board installation

Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 1.5 - 25 mm², flexible with ferrules to DIN 462282.5 - 16 mm², solid Stripping length (main cable) 14 mm Electrical rating

Rated breaking capacity at 400/415 V (cos phi to IEC 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DMM-63/4+SK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.