

INDUSTRIAL COMPONENT DATA

QM63/6 1319806 Y8-1319806 EATON ELECTRIC

Switch-disconnector, 6p, 63A

Brand: EATON - MOELLER | Manufacturer Part Number: QM63/6



Manufacturer	EATON - MOELLER
MPN / Reference	QM63/6
Catalog number	Y8-1319806
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-E89F1FC6EA
Generated	2026-08-05

Product Overview

Switch-disconnector, 6p, 63A

QM63/6

Eaton QM Switch-disconnector, QM, 50 A, 6 pole, without rotary handle, With drive shaft, 6 mm square

Switch-disconnector QM63/6, multi-pole switch, 6 poles, free air thermal current Ithe 50 A, with operating shaft, 6mm square

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton QM Switch-disconnector Catalog Number 1319806 Model Code QM63/6 EAN 8711426100381

Product Length/Depth 130 mm Product Height 90 mm Product Width 130 mm Product Weight 0.8 kg Certifications IEC/EN 60947-3

CE

IEC/EN 60947

RoHS

IEC/EN 60204

VDE 0660 Features & Functions

Fitted with: Drive shaft Functions Optional Stop Function Number of poles Six-pole General

Accessories Auxiliary contact or neutral conductor fitted by user. Actuator type Other Degree of protection NEMA Other

Degree of protection (front side) IP20 Mounting method Top-hat rail mounting

Rear mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 6000 V Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1

Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 1 x (2.5 - 10) mm², flexible

2.5 - 16 mm², solid Stripping length (main cable) 10 mm Tightening torque 1.8 Nm, Screw terminals, Main cables Tightening torque 1.8 Nm, Screw terminals, Main cables Electrical rating

Rated conditional short-circuit current (Iq) 15 kA Rated insulation voltage (Ui) 690 V Rated operational power at AC-23A, 400 V, 50 Hz 22 kW Rated operational power at AC-3, 380/400 V, 50 Hz 18.5 kW Rated operational volt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / QM63/6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.