

INDUSTRIAL COMPONENT DATA

T0-1-8218/Z 009559 Y7-9559 EATON ELECTRIC

Changeoverswitches, Contacts: 2, 20 A, front plate: 1-0-2, 90 °, m..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-8218/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-8218/Z
Catalog number	Y7-9559
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-E9F8B7F278
Generated	2026-08-02

Product Overview

Changeoverswitches, Contacts: 2, 20 A, front plate: 1-0-2, 90 °, maintained, rear mounting

Switch 2-pole switch 20 A Indicator plate: 1-0-2 90°

Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, rear mounting, 1 contact unit(s), Contacts: 2, 90 °, maintained, With 0 (Off) position, 1-0-2, Design number 8218

Changeover switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 2, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 009559 Model Code T0-1-8218/Z EAN 4015080095590 Product Length/Depth 118 mm Product Height 48 mm Product Width 48 mm Product Weight 0.112 kg

Certifications CSA-C22.2 No. 94

UL File No.: E36332

IEC/EN 60947

VDE 0660

UL 60947-4-1

CSA

CSA Class No.: 3211-05

CSA File No.: 012528

IEC/EN 60947-3

UL Category Control No.: NLRV

UL

CE

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{scw}) for a time of 1 second

ETIM for 009559 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

1

With zero (off) position (EF001416)

true

With retraction in 0-position (EF002428)

false

Rated permanent current I_u (EF001389)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

true

Suitable for front mounting (EF007246)

false

Suitable for distribution board installation (EF007262)

false

Suitable for intermediate mounting (EF007264)

true

Complete device in housing (EF007317)

false

Housi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-8218/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.