

INDUSTRIAL COMPONENT DATA

T0-3-15680/EA/SVB 038875 Y7-38875 EATON ELECTRIC Main switch, 3 pole + N + 1 N/O + 1 N/C, 20 A, Emergency-St..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15680/EA/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-15680/EA/SVB
Catalog number	Y7-38875
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-E34761C373
Generated	2026-08-02

Product Overview

Main switch, 3 pole + N + 1 N/O + 1 N/C, 20 A, Emergency-Stop function, 90 °, Lockable in the 0 (Off) position, flush mounting

General Switch 3 Pole + N + 1 NO + 1 NC 20 A 90° Mounting

Main switch, T0, 20 A, flush mounting, 3 contact unit(s), 3 pole + N, 1 N/O, 1 N/C, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T0, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 3 pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, T0, 20 A, flush mounting, 3 contact unit(s), 3 pole + N, 1 N/O, 1 N/C, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) positionMain switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T0, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 3 pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL,

Switch-disconnector according to IEC/EN 60947-3

General specificationsProduct nameEaton Moeller® series T0 Main switchPart

no.T0-3-15680/EA/SVBEAN4015080388753Product Length/Depth120 millimetreProduct height74 millimetreProduct width65 millimetreProduct weight0.142 kilogramCertificationsCSA-C22.2 No. 94

CSA File No.: 012528

VDE 0660

IEC/EN 60204

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 3211-05

IEC/EN 60947

UL File No.: E36332

UL Category Control No.: NLRV

UL

CSA

IEC/EN 60947-3

CE

CSA

ULProduct TradenameT0Product TypeMain switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand

Current (Icw) for a time of 1 secondFeatures & FunctionsFeaturesVersion as maintenance-/service switch

Version as main switch

Version as emergency stop installationFitted with:Red ro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15680/EA/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.