

## INDUSTRIAL COMPONENT DATA

# T0-4-8294/EZ 072069 Y7-72069 EATON ELECTRIC

## Changeoverswitches, Contacts: 8, 20 A, front plate: 1-0-2, 90 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-8294/EZ



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-4-8294/EZ    |
| Catalog number  | Y7-72069        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-8DEAF784DE   |
| Generated       | 2026-08-02      |

## Product Overview

Changeoverswitches, Contacts: 8, 20 A, front plate: 1-0-2, 90 °, maintained, centre mounting

Switch Switch 8 poles 20 A Indicator plate: 1-0-2 90°

Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, centre mounting, 4 contact unit(s), Contacts: 8, 90 °, maintained, With 0 (Off) position, 1-0-2, Design number 8294

Changeover switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Disconnectors and Cam Switches

## Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 072069 Model Code T0-4-8294/EZ EAN 4015080720690 Product Length/Depth 125 mm Product Height 48 mm Product Width 48 mm Product Weight 0.177 kg

Certifications CSA

UL File No.: E36332

UL  
CE  
CSA Class No.: 3211-05  
IEC/EN 60947  
CSA-C22.2 No. 60947-4-1-14  
IEC/EN 60204  
UL 60947-4-1  
CSA-C22.2 No. 94  
UL Category Control No.: NLRV  
CSA File No.: 012528  
IEC/EN 60947-3  
VDE 0660 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second  
ETIM for 072069 Low-voltage industrial controls and switchgear (EC001105)  
Feature Name  
Feature Value  
Model (EF000010)  
Reverser  
Number of poles (EF001391)  
4  
With zero (off) position (EF001416)  
Yes  
With retraction in 0-position (EF002428)  
No  
Rated permanent current Iu (EF001389)  
20 A  
Rated operation current Ie at AC-3, 400 V (EF001392)  
11.5 A  
Rated operation power at AC-3, 400 V (EF001364)  
4 kW  
Degree of protection (IP), front side (EF003118)  
IP65  
Degree of protection (NEMA), front side (EF011961)  
12  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of auxiliary contacts as change-over contact (EF003531)  
0  
Suitable for floor mounting (EF007243)  
No  
Suitable for front mounting (EF007246)  
Yes  
Suitable for distribution board installation (EF007262)  
No  
Suitable for intermediate mounting (EF007264)  
No

Complete device in housing (EF007317)

No

Housing material (EF...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-8294/EZ with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.