

INDUSTRIAL COMPONENT DATA

T0-5-8453/IVS 034104 Y7-34104 EATON ELECTRIC Reversing multi-speed switches, Contacts 10, 20A, 2 speeds, 2 separ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-8453/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-5-8453/IVS
Catalog number	Y7-34104
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-B86A7C9557
Generated	2026-08-04

Product Overview

Reversing multi-speed switches, Contacts 10, 20A, 2 speeds, 2 separate windings, front plate: 2-1-0-1-2, 60°, maintained, service distribution board mount.

Multi-speed switch with 10-pole reversing 20 A 2 speed

Eaton Moeller® series T0 Reversing multi-speed switches, T0, 20 A, service distribution board mounting, 5 contact unit(s), Contacts: 10, 60°, maintained, With 0 (Off) position, 2-1-0-1-2, Design number 8453

Reversing multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 10, Degree of Protection: Front IP30, Design: service distribution board mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60°, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Reversing multi-speed switch Catalog Number 034104 Model Code T0-5-8453/IVS EAN 4015080341048 Product Length/Depth 120 mm Product Height 55 mm Product Width 54 mm Product Weight 0.205 kg Certifications CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

UL File No.: E36332

CE
UL 60947-4-1
IEC/EN 60947
UL
CSA Class No.: 3211-05
VDE 0660
CSA
CSA-C22.2 No. 94
CSA File No.: 012528
IEC/EN 60204
IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 034104 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Pole switch
Number of poles (EF001391)
3
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current Iu (EF001389)
20 A
Rated operation current Ie at AC-3, 400 V (EF001392)
11.5 A
Rated operation power at AC-3, 400 V (EF001364)
4 kW
Degree of protection (IP), front side (EF003118)
IP30
Degree of protection (NEMA), front side (EF011961)
2
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
Yes
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)

No
Housi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-8453/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.