

INDUSTRIAL COMPONENT DATA

T0-6-8455/Z 015757 Y7-15757 EATON ELECTRIC Multi-speed switches, Contacts: 12, 20 A, 2 speeds, 2 separate wi..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-6-8455/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-6-8455/Z
Catalog number	Y7-15757
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-CC3409F404
Generated	2026-08-04

Product Overview

Multi-speed switches, Contacts: 12, 20 A, 2 speeds, 2 separate windings, front plate: 0-1-2-3, 60 °, maintained, rear mounting

Multi-speed switch 12 poles 20 A 2 speeds 2 windings

Eaton Moeller® series T0 Multi-speed switches, T0, 20 A, rear mounting, 6 contact unit(s), Contacts: 12, 60 °, maintained, With 0 (Off) position, 0-1-2-3, Design number 8455

Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 12, Degree of Protection: Front IP65, Design: rear mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-2-3, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Multi-speed switch Catalog Number 015757 Model Code T0-6-8455/Z EAN 4015080157571 Product Length/Depth 166 mm Product Height 48 mm Product Width 48 mm Product Weight 0.235 kg

Certifications VDE 0660

IEC/EN 60947-3

CSA-C22.2 No. 94

CSA

UL Category Control No.: NLRV

CE

UL File No.: E36332

CSA Class No.: 3211-05

CSA File No.: 012528

UL

IEC/EN 60947

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 015757 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Pole switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

true

With retraction in 0-position (EF002428)

false

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

true

Suitable for front mounting (EF007246)

false

Suitable for distribution board installation (EF007262)

false

Suitable for intermediate mounting (EF007264)

true

Complete device in housing (EF007317)

false

H...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-6-8455/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.