

INDUSTRIAL COMPONENT DATA

T0-8-8352/E 016134 Y7-16134 EATON ELECTRIC On-Off switch, 16-pole, 20 A, 90 °, flush mounting

Brand: EATON - MOELLER | Manufacturer Part Number: T0-8-8352/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-8-8352/E
Catalog number	Y7-16134
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-009C5B1B38
Generated	2026-08-03

Product Overview

On-Off switch, 16-pole, 20 A, 90 °, flush mounting

ON-OFF Disconnect Switch 16 poles 20 A 90° Flush Mount

Eaton Moeller® series T0 On-Off switch, T0, 20 A, flush mounting, 8 contact unit(s), 16-pole, with black thumb grip and front plate

On-Off switch, Product range: On-Off switch, Part group reference: T0, with black thumb grip and front plate, 16-pole, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 8 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 On-off switch Catalog Number 016134 Model Code T0-8-8352/E EAN

4015080161349 Product Length/Depth 143 mm Product Height 48 mm Product Width 48 mm Product Weight 0.208 kg

Certifications CSA

CSA File No.: 012528

UL 60947-4-1

IEC/EN 60947-3

VDE 0660

CE
IEC/EN 60947
UL
CSA-C22.2 No. 94
UL Category Control No.: NLRV
UL File No.: E36332
CSA Class No.: 3211-05
CSA-C22.2 No. 60947-4-1-14
IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 016134 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
No
Version as maintenance-/service switch (EF006986)
No
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Rated operating voltage (EF001435)
1000 V
Rated permanent current I_u (EF001389)
20 A
Rated permanent current at AC-21, 400 V (EF009165)
20 A
Rated operation power at AC-3, 400 V (EF001364)
5.5 kW
Rated short-time withstand current I_{cw} (EF007050)
0.32 kA
Rated operation power at AC-23, 400 V (EF007027)
5.5 kW
Switching power at 400 V (EF009166)
5.5 kW
Conditioned rated short-circuit current I_q (EF001444)
6 kA
Number of poles (EF001391)
16
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-8-8352/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.