

## INDUSTRIAL COMPONENT DATA

# T0-8-8372/E 064950 Y7-64950 EATON ELECTRIC

## Changeoverswitches, Contacts: 16, 20 A, front plate: 1-2, 90 °, m..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-8-8372/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-8-8372/E     |
| Catalog number  | Y7-64950        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-51D70712F4   |
| Generated       | 2026-07-29      |

### Product Overview

Changeoverswitches, Contacts: 16, 20 A, front plate: 1-2, 90 °, maintained, flush mounting

Switch Switch 16 pole 20 A Indicator plate: 1-2 90°

Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, flush mounting, 8 contact unit(s), Contacts: 16, 90 °, maintained, Without 0 (Off) position, 1-2, Design number 8372

Changeover switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 16, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, front plate: 1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 8 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

### Additional Product Information

#### General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 064950 Model Code T0-8-8372/E EAN 4015080649502 Product Length/Depth 143 mm Product Height 48 mm Product Width 48 mm Product Weight 0.208 kg

Certifications IEC/EN 60947

CSA Class No.: 3211-05

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

VDE 0660

CSA

CSA File No.: 012528

UL

UL File No.: E36332

CSA-C22.2 No. 94

UL Category Control No.: NLRV

CE

IEC/EN 60204

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second

ETIM for 064950 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

8

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Rated permanent current I<sub>u</sub> (EF001389)

20 A

Rated operation current I<sub>e</sub> at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF00...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-8-8372/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.