

## INDUSTRIAL COMPONENT DATA

# T3-2-1/I2/SVA(S)-RT 207174 Y7-207174 EATON ELECTRIC

## Panic switches, 3 pole, 32 A, Cylinder lock SVA, front p..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-1/I2/SVA(S)-RT



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | T3-2-1/I2/SVA(S)-RT |
| Catalog number  | Y7-207174           |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-56ACC8B7E6       |
| Generated       | 2026-08-03          |

### Product Overview

Panic switches, 3 pole, 32 A, Cylinder lock SVA, front plate 0-1, 90 °, maintained, surface mounting, P

T3-2-1/I2/SVA(S)-RT

Eaton Moeller® series T3 Panic switches, T3, 32 A, surface mounting, 3 pole, with red thumb grip and yellow front plate, Cylinder lock SVA

Panic switch, Product range: Switch with locking mechanism, Part group reference: T3, Stop Function: Emergency switching off function, with red thumb grip and yellow front plate, Information about equipment supplied: with two keys, 3 pole, locking arrangement: Cylinder lock SVA, Notes: If the key is withdrawn in position 1 the switch can be switched off but not on again without the key., Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 2 contact unit(s) , Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

### Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Panic switch Catalog Number 207174 Model Code T3-2-1/I2/SVA(S)-RT EAN 4015082071745 Product Length/Depth 181 mm Product Height 107 mm Product Width 100 mm Product Weight 0.484 kg Certifications IEC/EN 60947 IEC/EN 60204

VDE 0660

IEC/EN 60947-3

ETIM for 207174 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

Yes

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Rated operating voltage (EF001435)

690 V

Rated permanent current  $I_u$  (EF001389)

32 A

Rated permanent current at AC-23, 400 V (EF011777)

32 A

Rated permanent current at AC-21, 400 V (EF009165)

32 A

Rated operation power at AC-3, 400 V (EF001364)

11 kW

Rated short-time withstand current  $I_{cw}$  (EF007050)

0.65 kA

Rated operation power at AC-23, 400 V (EF007027)

15 kW

Switching power at 400 V (EF009166)

15 kW

Conditioned rated short-circuit current  $I_q$  (EF001444)

1 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive integrated (EF006697)

No

Voltage release optional (EF007491)

No

Device construction (EF008240)....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-1/I2/SVA(S)-RT with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.