

**INDUSTRIAL COMPONENT DATA**

# T3-2-8150/E 018367 Y7-18367 EATON ELECTRIC Reversing switches, Contacts: 3, 32 A, front plate: Höher 0 Tiefe..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-8150/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T3-2-8150/E     |
| Catalog number  | Y7-18367        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-BF3540B287   |
| Generated       | 2026-07-29      |

## Product Overview

Reversing switches, Contacts: 3, 32 A, front plate: Höher&gt;0

3-pole inverter switch 32 A Indicator plate: Höher&gt;0

Eaton Moeller® series T3 Reversing switches, T3, 32 A, flush mounting, 2 contact unit(s), Contacts: 3, 45 °, maintained, With 0 (Off) position, with spring-return from both directions to 0, Höher&gt;0

Reversing switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 3, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, with spring-return from both directions to 0, front plate: Höher&gt;0

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

## Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Reversing switch Catalog Number 018367 Model Code T3-2-8150/E EAN 4015080183679 Product Length/Depth 91 mm Product Height 54 mm Product Width 61 mm Product Weight 0.172 kg

Certifications VDE 0660

CE

CSA File No.: 012528

UL File No.: E36332

UL 60947-4-1

IEC/EN 60947

IEC/EN 60947-3

CSA Class No.: 3211-05

CSA-C22.2 No. 94

UL Category Control No.: NLRV

UL

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14

CSA Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 018367 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

On/Off switch

Number of poles (EF001391)

2

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-8150/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.