

INDUSTRIAL COMPONENT DATA

T3-2-8177/E 078479 Y7-78479 EATON ELECTRIC Spring-return switch, Contacts: 4, 32 A, front plate: START 1-0-2..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-8177/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-8177/E
Catalog number	Y7-78479
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-8B4B36E0F6
Generated	2026-08-03

Product Overview

Spring-return switch, Contacts: 4, 32 A, front plate: START>1-0-2

Switch with 4-pole return 32 A Indicator plate:

Eaton Moeller® series T3 Spring-return switch, T3, 32 A, flush mounting, 2 contact unit(s), Contacts: 4, 45 °, momentary/maintained, With 0 (Off) position, with spring-return from both directions, START>1-0-2

Spring-return switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: momentary/maintained, With 0 (Off) position, with spring-return from both directions, 2 contact unit(s), Rated uninterrupted current: I_u= 32 A, front plate: START>1-0-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Spring-return switch Catalog Number 078479 Model Code T3-2-8177/E EAN 4015080784791 Product Length/Depth 91 mm Product Height 54 mm Product Width 61 mm Product Weight 0.172 kg

Certifications UL

CE

IEC/EN 60204

UL File No.: E36332

CSA-C22.2 No. 94

UL 60947-4-1

CSA

IEC/EN 60947-3

CSA Class No.: 3211-05

CSA File No.: 012528

UL Category Control No.: NLRV

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

VDE 0660 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 078479 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

2

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

32 A

Number of switch positions (EF000231)

5

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-8177/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.