

INDUSTRIAL COMPONENT DATA

T3-2-8211/EZ 003075 Y7-3075 EATON ELECTRIC

Changeoverswitches, Contacts: 4, 32 A, front plate: 1-0-2, 60 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-8211/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-8211/EZ
Catalog number	Y7-3075
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-84292F5EB4
Generated	2026-08-04

Product Overview

Changeoverswitches, Contacts: 4, 32 A, front plate: 1-0-2, 60 °, maintained, centre mounting

Switch Switch; 4 poles; 32 A; Indicator plate: 1-0-2; 60 °;

Eaton Moeller® series T3 Changeoverswitches, T3, 32 A, centre mounting, 2 contact unit(s), Contacts: 4, 60 °, maintained, With 0 (Off) position, 1-0-2, Design number 8211

Changeover switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Changeover switch Catalog Number 003075 Model Code T3-2-8211/EZ EAN 4015080030751 Product Length/Depth 113 mm Product Height 54 mm Product Width 61 mm Product Weight 0.179 kg

Certifications CSA

CSA-C22.2 No. 60947-4-1-14

CE
IEC/EN 60204
CSA Class No.: 3211-05
IEC/EN 60947-3
CSA-C22.2 No. 94
UL File No.: E36332
IEC/EN 60947
UL 60947-4-1
VDE 0660
UL Category Control No.: NLRV
CSA File No.: 012528
UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 003075 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Reverser
Number of poles (EF001391)
2
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current Iu (EF001389)
32 A
Rated operation current Ie at AC-3, 400 V (EF001392)
23.7 A
Rated operation power at AC-3, 400 V (EF001364)
12 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
No
Suitable for front mounting (EF007246)
Yes
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No

Complete device in housing (EF007317)

No

Housing material (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-8211/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.