

INDUSTRIAL COMPONENT DATA

T3-4-15682/ST/SVB 025526 EATON ELECTRIC Main switch, +steel enclosure, 6p+1N/O+1N/C, Ie 25A, handle red yell..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-15682/ST/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-15682/ST/SVB
Catalog number	025526
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-7E9B892664
Generated	2026-08-02

Product Overview

Main switch, +steel enclosure, 6p+1N/O+1N/C, Ie=25A, handle red yellow, 0-1, 90°

General Switch; 6 poles + 1 NO + 1 NC; 32 A; 90 °; Box mounting; Red/Yellow Lever; Lockable in position 0 (OFF) stainless steel

Cam switch according to IEC/EN60947-3, size T3 in steel sheet enclosure, 690 V/32A, degree of protection Front IP65, with red rotary handle and yellow locking collar, lockable in O position with 3 padlocks. Design general: insulating material-surface mounting enclosure , flush mounting, center mounting breaker. High-performance, robust, compact T cam switches are used in industry, the trades , and building services management. A variety of standard switches is available for selection. These are supplemented by special customer-specific switches. Here the possibilities are almost unlimited. Comprehensive accessories complete the switch product range and supplement the usage alternatives. All current paths are equipped with double-break contacts.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, +steel enclosure, 6p+1N/O+1N/C, Ie=25A, handle red yellow, 0-1, 90°Cam switch according to IEC/EN60947-3, size T3 in steel sheet enclosure, 690 V/32A, degree of protection Front IP65, with red rotary handle and yellow locking collar, lockable in O position with 3 padlocks. Design general: insulating material-surface mounting enclosure , flush mounting, centre mounting breaker. High-performance, robust, compact T cam switches are used in industry, the trades, and building services management. A variety of standard switches is available for selection. These are supplemented by special customer-specific switches. Here the possibilities are almost unlimited. Comprehensive

accessories complete the switch product range and supplement the usage alternatives. All current paths are equipped with double-break contacts. Delivery program

Product range Main switch

maintenance switch

Repair switch Part group reference T3 Stop Function Emergency switching off function With red rotary handle and yellow locking ring Number of poles 6 pole Auxiliary contacts 1 N/O 1 N/C Degree of Protection IP65 Design surface mounting Contact sequence Design number 15682 Function Motor rating AC-23A, 50 - 60 Hz [P] 400 V [P] 15 kW Rated uninterrupted current [I_u] 32 A Note on rated uninterrupted current I_u Rated uninterrupted current I_u is specified for max. cross-section. Number of contact units 4 contact unit(s) Technical data

General Standards according to IEC/EN 60 204-1 Part 1

IEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-di...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-15682/ST/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.