

INDUSTRIAL COMPONENT DATA

T3-9-SOND*/E 907858 Y7-907858 EATON ELECTRIC

Non-standard switch, T3, 32 A, flush mounting, 9 contact unit(s)

Brand: EATON - MOELLER | Manufacturer Part Number: T3-9-SOND*/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-9-SOND*/E
Catalog number	Y7-907858
Category	Switch disconnecter
Minimum order	10 Pcs
Document ID	EO-02A2034D13
Generated	2026-08-03

Product Overview

Non-standard switch, T3, 32 A, flush mounting, 9 contact unit(s)

T3-9-SOND*/E

Eaton Moeller® series T3 Non-standard switch, T3, 32 A, flush mounting, 9 contact unit(s)

Non-standard switch, Product range: Non-standard switch, Part group reference: T3, Notes: customized version according to form, Degree of Protection: Front IP65, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 9 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Non-standard switch Catalog Number 907858 Model Code T3-9-SOND*/E Product Length/Depth 171 mm Product Height 54 mm Product Width 61 mm Product Weight 0.486 kg Certifications IEC/EN

60947-3

VDE 0660

IEC/EN 60204

IEC/EN 60947

ETIM for 907858 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Rated operating voltage (EF001435)

690 V

Rated permanent current I_u (EF001389)

32 A

Rated permanent current at AC-23, 400 V (EF011777)

32 A

Rated permanent current at AC-21, 400 V (EF009165)

32 A

Rated operation power at AC-3, 400 V (EF001364)

11 kW

Rated short-time withstand current I_{cw} (EF007050)

0.65 kA

Rated operation power at AC-23, 400 V (EF007027)

15 kW

Switching power at 400 V (EF009166)

15 kW

Conditioned rated short-circuit current I_q (EF001444)

1 kA

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive integrated (EF006697)

No

Voltage release optional (EF007491)

No

Device construction (EF008240)

Built-in device fixed built-in technique

Suitable....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-9-SOND*/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.